



Especificaciones · Specifications · Spécifications · Spezifikationen

Resistencia a la abrasión <i>Abrasion resistance</i> Résistance à l'abrasion <i>Abriebfestigkeit</i>	ISO 12947 - 2 35.000 Ciclos Cycles Cycles Zyklen
Resistencia al pilling <i>Pilling resistance</i> Résistance au boulochage <i>Pillingbeständigkeit</i>	ISO 12945 - 2 5 No Pilling No pilling Pas de boulochage Kein Pilling
Desplazamiento costura <i>Seam slippage</i> Glissement de couture <i>Nahtverschiebung</i>	
Solidez al lavado <i>Maintenance - Cleaning</i> Entretien - Nettoyage <i>Wartung - Reinigung</i>	ISO 105 - C06 5 Excelente Excellent Excellent Ausgezeichnet
Solidez al frote <i>Rubbing fastness</i> Solidité au frottement <i>Reibechtheit</i>	ISO 105-X12 5 Excelente Excellent Excellent Ausgezeichnet
Solidez a la luz <i>Light fastness</i> Solidité à la lumière <i>Lichtechtheit</i>	ISO 105-B02 5 Excelente Excellent Excellent Ausgezeichnet
Encogimiento <i>Shrinkage</i> Rétrécissement <i>Einlaufen</i>	
Resistencia al desgarro <i>Tear Strength</i> Résistance à la déchirure <i>Weiterreißfestigkeit</i>	

Composición · Composition
Composition · Zusammensetzung

Composición <i>Composition</i>	PES 100%
Composición <i>Zusammensetzung</i>	
Peso(gr/m2) <i>Weigh</i>	328 gr/m2
Poids <i>Gewicht</i>	
Ancho pieza <i>Piece width</i>	140 cm
Largeur de la pièce <i>Stückbreite</i>	

Otras especificaciones · Other specifications · Autres spécifications
Weitere Spezifikationen

Ignífugo
Flame-retardant Sí | Yes | Oui | Ja
Ignífugo
Feuerfest

Fácil limpieza
Easy to clean Sí | Yes | Oui | Ja
Facile à nettoyer
Leicht zureinigen

EASYCLEANING

Limpieza · Cleaning · Nettoyage · Reinigung

Washing at or below
40 °C


Do not bleach

Dry clean
with PCEIron at low
temperatureTumble dry,
low heat

Colores · Colors · Couleurs · Farben ·



Albero 01



Albero 02



Albero 03



Albero 04